



This setup transforms the mobile platform to a smart locker system for secured deliveries.



Rated payload of up to 50 kg



**Loading volume** up to 110 L



**Lockable compartments** for secure deliveries



Manage access through NFC & QR-code reader



**VERSION: EN-1-1-6-2403-1.0** 

## Locker Accessory for uLog Lift 150



**uLog Locker** makes pick-up's and deliveries smooth and secure by protecting transported goods until they reach the desired recipient. That way uLog Locker can be used in versatile scenarios such as airports, hotels, retail, grocery, hospital, laboratories and offices.

## **Technical Specifications**

Dimensions	Length Width Height	600 mm 438 mm 875 mm
Payload	Rated Load	50 kg
Work Environment	Operating Temperature Charging Temperature Work Environment	-10°C - +65°C ; UV resistance; Corrosion resistant +5°C - +45°C (indoor) Indoor
Storage Conditions	Temperature	-20°C - +65°C
Network Communications	WIFI	Wifi module (AP6256) 2.4G&5GHz, support 802.11a/b/g/n/ac protocol
Electrical Power	Input	24 V (15-85 V range)
Weight	Empty	50 kg
Material	Body	Stainless steel (body), PLA (head)
Color	Body	Signal white shiny (body), Anthracite gray mate (head)
Display		7", resolution of 1024X600
Software		TruOS
IP Rating		IP44



## **Product Views**

